



Offer more with production level LED printing

Designed to drive productivity, the two-meter EFI™ VUTEK® GS2000Lx LED printer gives you the ability to print on thinner and specialty substrates while lowering costs.



High-definition imaging and LED technology

- Deliver high-definition P-O-P graphics with true 1000 dpi and multilayer white ink printing.
- Extend the range of supported substrates with innovative LED technology.
- Increase uptime, productivity and efficiency while reducing maintenance with instant on/off LED lamps.
- Drive down operating costs with decreased power consumption, fewer consumable parts and less waste, while printing consistent color output with simpler operation.
- Satisfy customer requests for a greener print solution.

Continuous print productivity

- Take on more jobs and turn them faster with continuous print productivity.
- Accurately align images on single- or double-sided rigid material using the precision alignment fence.

Increased reliability, consistency and performance

- Maximize uptime with fewer parts, improved reliability standards and easy troubleshooting.
- Run multiple jobs at once with multi-queue functionality available at the user interface.
- Integrate your VUTEK printer with EFI Web-to-Print and MIS/ERP solutions with native JDF connectivity.

Features and benefits

- Production-level LED technology
- Eight-color plus two white and single-pass, multilayer printing
- Switchable to Fast-5 for high productivity
- Dual resolution: TRUE 600 dpi (24pL) or 1000 dpi (12pL) selectable
- Output up to 2,000 ft²/hr (186 m²/hr) and 45 – 4'x8' (1.2m x 2.4m) sheets per hour
- Optional variable drop grayscale print capability

Media/Handling

- Handles flexible and rigid media up to 80" (2 m) wide and up to 2" (5.08 cm) thick
- Optional extension table with casters and small depth extension table

Productivity

- Fast-5: 2,000 ft² (186 m²) per hour
 - Production up to 45 – 4'x8' (1.2m x 2.4m) boards per hour
- Eight-color plus white: 1,000 ft² (93 m²) per hour
 - Production up to 24 – 4'x8' (1.2m x 2.4m) boards per hour

EFI Fiery proServer

- Optimized for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery XF RIP and printer allows back communication of audit information on every print job
- Powerful production tools, such as nesting, step and repeat, scaling, cropping, and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color

EFI Inks

- Supplied in 5.0-liter containers.
- Expanded gamut CMYK pigments for world-class pantone matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business hour (3-business day) response
- Eligible for upgrade to:
 - Critical: Providing 8-business hour (1-business day) response
 - ProActive: Providing 16-business hour (2-business day) response

Environmental considerations

- Compressed Air: 100–150 psi maximum at 12 cf/m—dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68° F to 86° F (20° C to 30° C)
- Humidity: 40% to 80% (noncondensing)
- Machine Weight: 5050 lbs. (2291 kg)
- Height: 66" (1676 cm)
- Width: 202" (513.08 cm)
- Depth: 63" (160 cm), 163" (414 cm) with tables
 - + 5" (12.7 cm) unwinder
 - + 5" (12.7 cm) rewinder
- Electrical: 3-Phase, 60 amps @ 200–230 volt supply or 30 amp @ 400–460 volt supply

EFI fuels success.

From Fiery to super wide inkjet, from the lowest cost per label to the most automated business processes, EFI has everything your company needs to succeed. Visit www.efi.com or call 650-357-3500 for more information.



The APPS logo, AutoCal, Auto-Count, Balance, Best, the Best logo, BESTColor, BioVu, BioWare, ColorPASS, Colorproof, ColorWise, Command WorkStation, CopyNet, Cretachrom, Cretaprint, the Cretaprint logo, Cretaprinter, Cretaroller, DockNet, Digital StoreFront, DocBuilder, DocBuilder Pro, DocStream, DSFdesign Studio, Dynamic Wedge, EDOX, EFI, the EFI logo, Electronics For Imaging, Entrac, EPCount, EPPPhoto, EPRegister, EPStatus, Estimate, ExpressPay, Fabrivu, Fast-4, Fiery, the Fiery logo, Fiery Driven, the Fiery Driven logo, Fiery JobFlow, Fiery JobMaster, Fiery Link, Fiery Prints, the Fiery Prints logo, Fiery Spark, FreeForm, Hagen, Inkintensity, Inkware, Jetrion, the Jetrion logo, LapNet, Logic, MiniNet, Monarch, MicroPress, OneFlow, Pace, PhotoXposure, Printcafe, PressVu, PrinterSite, PrintFlow, PrintMe, the PrintMe logo, PrintSmith, PrintSmith Site, Printstream, Print to Win, Prograph, PSI, PSI Flexo, Radius, Rastek, the Rastek logo, Remoteproof, RIPChips, RIP-While-Print, Screenproof, SendMe, Sincrolor, Splash, Spot-On, TrackNet, UltraPress, UltraTex, UltraVu, UV Series 50, VisualCal, VUTEK, the VUTEK logo, and WebTools are trademarks of Electronics For Imaging, Inc. and/or its wholly owned subsidiaries in the U.S. and/or certain other countries.