

Dye-Sublimation Printer




HIGH-PRODUCTION AND HIGH-PRECISION



The 190cm wide ZT-1900 is designed for the most demanding textile print environments. Print incredible colours for hundreds of applications, at speeds of 220sqm/hr in draft mode and 150sqm/hr in production mode.

Visit **www.rolanddg.eu** for further information







FASHION







INTERIOR DÉCOR

| Model | | ZT-1900 | |
|----------------------------------|---|--|--|
| Printing Technology | | 4 double-channel Kyocera | |
| Media | Width | 190 cm | |
| | Paper Feed | From 15gr/sqm to 220gr/sqm | |
| | Roll outer diameter | 730mm (back) 600mm (front) | |
| | Roll weight | Max. 450 kg | |
| | Core diameter | 3" | |
| Ink | Туре | Water-Based Dye-Sublimation Ink | |
| | Capacity | 5Kg pouch inside card box, replace on run | |
| | Colours | CMYK (Mirror configuration) | |
| Print resolution (dots per inch) | | 600 x 300 600 x 600 600 x 900 | |
| Connectivity | | Ethernet | |
| Power requirements | | 380V 32A 4P+E | |
| Power consumption | During operation | Approx. 1500 W | |
| | IR Lamp | Approx. 1500 W | |
| Dimensions of Printer | Length | 4089 mm | |
| | Width | 1254 mm (1792 mm with the external winding/ unwinding system mounted) | |
| | Height | 1824 mm | |
| Recommended Installation Area | | 6 x 3 metres (to allow 1 metre clearance all around the printer to open the doors) | |
| Weight of Printer | | 1400 kg | |
| Environment | Power on | Temperature: 20 to 25°C , humidity: 40% to 80% RH (no condensation) | |
| Included items | | 21" monitor, Operator Control Station inside the printer, gun for air compressor, power cable. | |
| RIP | Optional Ergosoft Roland Edition 3 Special Plus. Others RIPS, consult with RIP vendors | | |

| Print Modes | Resolution | Pass | Speed | | |
|--------------------|------------|------|-----------|--|--|
| 4 Colour CMYK | | | | | |
| High Speed | 600 x 300 | 1 | 220 sqm/h | | |
| High Speed | 600 x 300 | 1,1* | 195 sqm/h | | |
| Production Quality | 600 x 600 | 2 | 150 sqm/h | | |
| Production Quality | 600 x 600 | 2,1* | 120 sqm/h | | |
| High Quality | 600 x 900 | 4,1* | 90 sqm/h | | |

* Pass Control Nesting. Percentage of nozzles nesting between passes.

| ErgoSoft Roland Edition 3 System Requirements (RIP is an optional purchase) | | | | |
|---|---|--|--|--|
| Operating system | Windows® 10 (32/64-bit) | | | |
| CPU | Intel® Core™ i7-7700K (4.2 GHz) Socket 1151 or faster recommended | | | |
| RAM | 8GB or more recommended on 32-Bit - 16GB or more recommended on 64-Bit | | | |
| Video card and monitor | Display resolution of 1600 x 900 or higher recommended | | | |
| Free disk space (HDD/SSD) | 2 Solid State Disks (SSD) recommended. 512 GB to run the program installation 512 GB to store ripped data and spooling data | | | |
| Consumables | | | | |
| Model | Description | | | |
| INKU-ZTS-5000-CY | INKU ZTS Dye Sublimation Ink Cyan, 5000 gr | | | |
| INKU-ZTS-5000-MG | INKU ZTS Dye Sublimation Ink Magenta, 5000 gr | | | |
| INKU-ZTS-5000-YE | INKU ZTS Dye Sublimation Ink Yellow, 5000 gr | | | |
| INKU-ZTS-5000-BK | INKU ZTS Dye Sublimation Ink Black, 5000 gr | | | |

Specifications, designs and dimensions listed may be subject to change without notice.

Enjoy the peace of mind of having one of the most comprehensive warranty packages in the industry, included with the ZT-1900.

Roland DG reserves the right to make changes in specifications, materials or accessories without notice. Actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland DG dealer for details. No guarantee or warranty is implied other than expressly stated. Roland DG shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. PANTONE[®] is the property of Pantone LLC. All other trademarks are the property of their respective owners. Reproduction or use of copyrighted material is governed by local, national, and international laws. Customers are responsible for observing all applicable laws and are liable for any infringement. Roland DG Corporation has licensed the MMP technology from the TPL Group.

Specifications





Sweden

Phone +46(0)40-672 84 00

E-mail: info@marabu.se

www.marabu.se

AUTHORISED DEALER:

Finland Phone +358-9 279 85 40 E-mail: info@marabu.fi www.marabu.fi

SELECTED IMAGES BY: